

OSCON: AN OPERATING SYSTEM CONSULTANT*

Louise Guthrie, Paul Mc Kevitt and Yorick Wilks

Computing Research Laboratory
Dept. 3CRL, Box 30001,
New Mexico State University
Las Cruces, NM 88003-0001, USA.
CSNET: paul@nmsu.edu [505-646-5109]

ABSTRACT

One of the most useful applications of natural language interface technology is the area of computer consultants. Computer consultants are programs which a user can ask for help about some topic. One of the easiest ways to interact with computer consultants is by typed English. These programs can give answers in English too. We have developed a computer consultant called OSCON (Operating System CONSULTant) which gives English answers to English queries about computer operating systems. The program currently answers over 1000 queries for over 40 commands from the UNIX† and MS-DOS‡ operating systems. OSCON answers a wide variation of queries that users may wish to ask. OSCON is intended to be a consultant for various types of users who may ask vague and detailed queries. The OSCON system is one of the most advanced natural language interfaces for operating system help available today. OSCON is programmed in Quintus Prolog and does not take more than 2.5 seconds to answer a query.

KEYWORDS

Natural language interface's, Operating Systems, Information retrieval.

INTRODUCTION

This paper describes the OSCON (Operating System CONSULTant) program (OSCON[1,2]) and its capabilities. OSCON is a natural language interface which answers English queries about computer Operating Systems (see Mc Kevitt, 1986; Mc Kevitt, 1988; Mc Kevitt & Wilks, 1987). OSCON allows the user to enter English queries and then answers them in English. The program is written in Quintus Prolog, runs on a Sun-3/ME-4 computer, and the maximum time taken to answer a given query is 2.5 seconds. OSCON answers over 1000 queries for over 40 commands from the UNIX and MS-DOS Operating Systems. There are four basic types of query a user can ask and the system handles all of these. OSCON will also answer queries about options on UNIX commands and

complex queries about command compositions. The system is intended to be used by varying types of users with different levels of expertise. The architecture of OSCON is modular so that it is easily updated and can be easily mapped over to other domains.

QUERY COVERAGE OF OSCON

The problem with building effective natural language interfaces is that there are many ways of asking English queries. The system must attempt to capture all the different possibilities. One way to do this is to capture the basic types of queries that people ask. This gives the system the power of answering a large number of queries when it caters for each type.

There are four basic types of query that people ask about Operating Systems. These are: (1) what-is-attribute of mentioned command (e.g. "What does rm do?"), (2) what-is mentioned command (e.g. "What is more?"), (3) what-is-command for mentioned effect (e.g. "How do I see my file on the printer?"), and (4) what-is mentioned concept (e.g. "What is a file?"). There are three cases of type (1): (1) what-is-effect (e.g. "What does rm do?"), (2) what-is-syntax (e.g. "What is the syntax of cp?"), and (3) what-is-precondition (e.g. "What is needed for rm?"). Each of these basic query types can also be asked in terms of options. Examples are, "What option of 'ls' shows the number of bytes in my files?" (what-is-option + mentioned command), "What does ls -l do?" (what-is-effect + option), "How do I rename a file without having reported errors?" (what-is-command + option), "What are the options on ls?" (what-are-options), "What does the -i option normally do?" (what-is mentioned concept). Users can also ask queries involving command compositions. An example is, "How do I list my files and print them on the printer?" This query involves a query about listing files (what-is-command) and then printing them on the printer (what-is-command).

The OSCON program currently answers (1) the four basic query types, (2) queries about options, and (3) command

*This research is currently funded by U S WEST Advanced Technologies, Denver, Colorado, under their Sponsored Research Program.

†UNIX is a trademark of AT&T Bell Laboratories.

‡MS-DOS is a trademark of Microsoft Corporation.

composition queries for both the UNIX and MS-DOS Operating Systems. The fact that queries are of a given type aids in understanding and generating answers to them. For example, queries of type (1) above will always include a command name. Therefore, the parser for OSCON could check for command names and if it found them, then discover that the query was of type (1). Also, the generator would generate an answer, in a particular format, depending on the type of query. Rules of thumb such as these also speed up the time it takes OSCON to answer queries. Although one can add such rules of thumb into the interface it does not reflect a short-cut to natural language parsing. For example, there is no such short cut to understanding the query, "How do I print a file on the Imagen with no page burst?" Understanding queries is a combination of both (1) filtering the query type, and then (2) understanding the query. Examples of queries answered by OSCON[1.2] are shown in Appendix A (p. 11). These examples are listed by query type.

THE ARCHITECTURE OF OSCON

The architecture of the OSCON system is well defined and exists as six distinct modules. There are two arguments for modularizing any system: (1) It is much easier to update the system at any point, and (2) it is easier to map the system over to another domain. The six modules in OSCON are as follows: (1) **ParseCon**: natural language syntactic grammar parser which detects query-type, (2) **MeanCon**: a natural language semantic grammar which determines query meaning, (3) **KnowCon**: a knowledge representation for understanding, (4) **DataCon**: a knowledge representation for solving, (5) **SolveCon**: a solver for resolving query representations against knowledge base representations, and (6) **GenCon**: a natural language generator for generating answers in English.

ParseCon consists of a set of programs which read natural language input and determine the type of query being asked by the user. We have described the four basic types of query in the "Query coverage of OSCON" section above. For each type of query there are tests for characteristic ways of asking that query.

MeanCon consists of programs which check queries for important information. There are predicates which check for mentioned (1) command names (e.g. "ls", "more"), (2) command-effect specifications (e.g. "see a file"), and (3) concepts (e.g. "file", "directory"). In case (2) there are specific types of information searched for: (1) **verb** specifying action (e.g. "see", "remove"), (2) **object** of action (e.g. "file"), (3) **modifier** of object (e.g. "contents"), and (4) **location** of object (e.g. "screen"). **MeanCon** also checks for option verbs (e.g. "number") and option verb objects (e.g. "lines"). **MeanCon** contains a dictionary of English words that define categories such as "person", "modifier", "article", "quantifier" and "prepositions".

KnowCon consists of a set of data files to represent the knowledge about the domain language used for understanding English queries. Files contain information about verbs which categorize types of command or action.

Examples of categories of action are: (1) creating, (2) screenlisting, (3) printerlisting, (4) sending, (5) transferring, and (6) removing. **KnowCon** also contains grammar rules for Operating System objects like "date", "file" and "directory". The grammar rules encode characteristic ways in which people talk about the objects in English.

DataCon consists of a set of data files defining detailed information about Operating System commands. This information is stored for the UNIX and MS-DOS Operating Systems. The data for UNIX is split among seven files: (1) command preconditions, (2) command effects, (3) command syntax, (4) command names, (5) command precondition options, (6) command effect options, and (7) command name options. The first four files contain basic data about commands while the last three contain data for options. For MS-DOS, data is contained in just four files which are similar to the first four here.

SolveCon is a solver which constructs and matches representations of user queries (called Formal Queries) against **DataCon** and produces an instantiated Formal Query which serves as an answer for the query. **SolveCon** is the driver of the OSCON program because it contains the information for mapping English sentences into instantiated answers. It contains a set of complex rules which call other OSCON modules to determine (1) query type, and (2) the instantiated Formal Query for that query.

GenCon is the natural language generator for OSCON and maps instantiated information from **SolveCon** into English answers. Here, there are algorithms for printing out (1) preconditions, (2) effects, and (3) syntax of commands. Also, there are routines for printing out examples of the use of commands and command compositions. The type of query asked by the user determines the information mapped to the user.

KNOWLEDGE REPRESENTATION IN OSCON

One of the problems in building natural language interfaces is to organize the knowledge of the domain in some form which will be effective. There are two types of knowledge stored in OSCON: (1) knowledge about language, and (2) knowledge about Operating Systems.

The knowledge about language stored includes words used to refer to command actions. For example, a user may use the words "delete", "remove", "get rid of", "erase" and so on to ask a query about deleting files and directories. These words must be stored under the general category of delete. Also, there are many ways in which people ask queries about actions. For example, if you are asking about copying a file you will probably specify the file which you wish to copy. If you are asking about "displaying" you will specify what you wish to display and where you wish to display it. This type of knowledge is called "understanding knowledge" and is stored within a module of OSCON called **KnowCon**.

More detailed knowledge about Operating Systems is contained in a database called **DataCon**. This type of knowledge includes command preconditions, command effects, command syntax, and the names of commands. Also,

stored here is (1) knowledge about options for commands, (2) English descriptions of Operating System concepts like “files” and “directories”, and (3) knowledge about plans or possible command combinations (e.g. ‘ls’ can precede ‘lpr’ but the converse is not true). The knowledge stored here is for the UNIX and MS-DOS Operating Systems. The distinction between the two types of knowledge is that one is language oriented and the other is domain oriented. One type of knowledge is used for understanding queries and the other for solving queries. This is the principle of separation of understanding and solving defined in Hegner (1988).

Knowledge for understanding (KnowCon)

There are two types of understanding knowledge stored in the KnowCon module: (1) data on Operating System action reference, and (2) data on descriptions of Operating System objects. The first type of knowledge includes sets of words or phrases that may refer to some operating system action or command. For example, the words, “print”, “print out”, and “get a copy” would indicate that the user was referring to printing something on the printer. Such words and phrases are stored as being associated with the general concept of printing. The second type of knowledge is used for defining the ways that users refer to Operating System objects. For convenience the data has been split up into two types (a) data on files and directories, and (b) data on other Operating System objects. In type (a) there are grammar rules specifying how users refer to files and directories, and in type (b) there are rules for how users refer to other Operating System objects.

Referring to actions

In asking queries about Operating Systems users commonly use a well defined set of verbs or verb phrases. For example, if a user wants to know about removing files or directories he/she will use the following verbs and phrases: “delete”, “remove”, “get rid of”, “erase” and so on. Queries about copying may be referenced by: “copy”, “transfer”, and “move”. These phrases should be captured by the OSCON program. Phrase and words are stored under their categories in the KnowCon module of the program.

It is possible to divide the set of Operating Systems commands into various categories. We have defined three major command categories and each of these have various subdivisions. The three categories are “listing”, “altering” and “compiling” commands. Listing commands are those which display information about the state of files in an Operating System. Altering commands are used to alter the state of files in the system. Compiling commands are used to compile files in the system rather than display/alter them. There are two types of listing command, (1) screenlisting, and (2) printerlisting. Screenlisting commands are those which allow the user to see information on the screen and printerlisting will do the same for the printer. There are three subtypes of screenlisting command, (1) display-file (e.g. “more”, “nroff”, “cat”), (2) display-file/directory-information (e.g. “ls”), and (3)

display-system-information (e.g. “users”, “who”, “ps”, “jobs”). There is only one subtype of printerlisting command (e.g. “lpr”, “runoff*”, “itroff”).

Altering commands are of three types, (1) creating (e.g. “gemacs”, “vi”, “mkdir”), (2) removing (e.g. “rm”, “rmdir”, “kill”), and (3) transferring (e.g. “mv”, “cp”). Each of these can be applied to either files or directories. A third type of command is compiling commands. These commands cannot be categorized under altering commands as they are really utilities which do not change files but use them. An example of such a command is “run”.

It is important to point out that certain commands apply to files which are not directories and others only apply to files which are directories. For example, “more” can only be used on files and not directories and “rmdir” can only be used on directories and not files. Such information can be used to specify the preconditions for commands and enables the system the capability to detect errors in user queries and inform the user about such errors. For example, if a user asked, “How do I use “more” to display a directory?” the system could locate that the precondition for “more” is that it only works over files. Then the system could tell the user this information.

The rules listed below are examples of typical action rules in KnowCon. Rules [1] and [2] show typical verb phrasings used to reference the action of screenlisting. Rule [3] is for printerlisting, and rules [4] and [5] for creating.

- [1] screenlist --> [see].
- [2] screenlist --> [look, at].
- [3] printerlist --> [print].
- [4] create --> [edit].
- [5] create --> [produce].

Referring to objects

Queries about Operating Systems often include reference to operating system objects like files and directories. Typically, users will refer to the object which is operated over by some command. The phrasing of the English query will dictate the object present. KnowCon has objects separated into two categories: (1) file/directory object specifications, and (2) other Operating System object specifications.

The rules listed below are examples of file/directory object specifications. File object specifications include grammar rule definitions for files and directories. The first rule definition below [1] specifies that a file can be mentioned in a query by the word “file” preceded by three modifiers. The first modifier can be (1) a quantifier (e.g. “all”, “some of”), and the second (2) a possessive (e.g. “my”, “our”). Then **filemod** can be a modifier of type of file. Examples are “mail”, “device”, “plain”, “executable” and so on. This grammar rule will capture most of the ways that a user might refer to a file.

The second rule [2] shows that a directory may have two modifiers and then the word referring to directory itself.

*“runoff” is a command defined at the Computing Research Laboratory to load text formatting packages for word processing a text file.

Rule [3] shows that a file or directory could be in reference. This happens because it is ambiguous as to whether the intended referent is file or directory. The user, by using the plural of file may intend directory* rather than the plural for file. Rule [4] defines location to be a triple: (1) preposition (prep), (2) modifier (mod), and (3) directory (dir). Phrases like “..in my directory”, “..in our directory”, and “..in the directory” will match here. There are more specific definitions of location for where the location is. Rule [5] is a definition of screen location in terms of (1) preposition (prep), (2) modifier (mod), and (3) screen-output (soutput). Preposition and modifier are self explanatory and output is the location of output. This could be “terminal” or “screen”. Rule [6] is the equivalent definition for a printer location. The output specification here is for a printer. Then poutput can be (1) “printer”, (2) “imagen” or (3) “laser writer”.

- [1] file --> mod, mod, filemod, [file].
- [2] directory --> mod, mod, [directory].
- [3] fileordir --> mod, mod, filemod, [files].
- [4] location --> prep, mod, dir.
- [5] slocation --> prep, mod, soutput.
- [6] plocation --> prep, mod, poutput.

The second type of object definitions include objects other than those to do with files and directories. Some examples are shown below. Rule [1] shows the definition of a queue in terms of (1) a modifier, followed by (2) [printer, queue]. There are definitions of users by rules [2] and [3]. Rules [4] and [5] define names. The definitions of objects are simply definitions of the various ways with which users refer to the objects.

- [1] queue --> mod, [printer, queue].
- [2] users --> names, mod, [users], prep, mod, [system].
- [3] users --> names, [system, users].
- [4] names --> mod, [names, of].
- [5] names --> [].

Knowledge for solving (DataCon)

The knowledge for solving in OSCON consists of files of data that describe detailed information about Operating Systems. There are four types of knowledge stored here (1) Basic command representation, (2) Option representation, (3) Concept representation, and (4) Plan representation.

Basic command representation

There are basically four types of information about any command held in the database. These are (1) Preconditions, (2) Effects or Postconditions, (3) Syntax, and (4) Command Names. Preconditions are lists of objects that are necessary for a command to be executed. Here are some examples of preconditions for commands from UNIX. Rules [1] and [2] show that “more” and “cat” have the precondition, “file”. The command, “mkdir” has the precondition “directory” and “cp” has

*A directory is a set of files.

no precondition.

- [1] precon(more, [file]).
- [2] precon(cat, [file]).
- [3] precon(mkdir, [directory]).
- [4] precon(cp, []).

Effects, or postconditions, are definitions of the outcome of commands. The effect is defined by a predicate which has a name and three arguments. The predicate name is the action and the arguments are (1) object, (2) object modifier, and (3) location. The rules below show some effects for UNIX commands. Rule [1] shows the effect for the command “more”. The object for “more” is “file” and its modifier “contents”. The location of output of “more” is the “screen”. One case of the “cat” command [2] has the same effect as “more”. The other effect case of “cat” [3] is defined as concatenate and describes the concatenation of files together. The command “ls” will either display directory contents [4], or file information [5] on the screen. The displaying-information command “users” will display usernames on the screen. Rule [7] describes the “gemacs” command which creates files, and rule [8] the “rm” command which deletes them.

- [1] comm(more, display(file, contents, screen)).
- [2] comm(cat, display(file, contents, screen)).
- [3] comm(cat, concat(file1, file2, file3)).
- [4] comm(ls, display(directory, contents, screen)).
- [5] comm(ls, display(file, info, screen)).
- [6] comm(users, display(usernames, @, screen)).
- [7] comm(gemacs, create(file, @, loc)).
- [8] comm(rm, remove(directory, @, loc)).

The syntax of commands is defined as a structure which contains the name of some command and then its syntactic definition of use. Shown below are some examples of the syntax for UNIX commands. The syntax rules are three place lists containing (1) Command name, (2) Optionname (filled in from context), and (3) Syntax description.

- [1] syn(more, Optionname, "[more <filename>]").
- [2] syn(cat, Optionname, "[cat <filename>]").
- [3] syn(ls, Optionname, "[ls <directoryname>]").
- [4] syn(users, Optionname, "[users]").
- [5] syn(gemacs, Optionname, "[gemacs <filename>]").

Option representation

DataCon also contains information for option specifications of commands. DataCon has files for (1) Option Preconditions, (2) Option Effects, (3) Option Names. There is no distinction for option syntax as this is practically the same for commands with options or not.

Option Preconditions are defined as three place lists with the (1) Command Name, (2) Option name, and (3) Precondition List. Shown below are a set of options for the various commands. The Precondition List contains the objects which must be present for the command to be executed. Rules [1],[2] and [3] show that each option for “cat” has “file” as precondition. Rules [4] and [5] show

that for one option of “cp” (i) there is no precondition, and for the other option (r), “directory” is the precondition. Rules [6] and [7] show the preconditions for “ls”.

- [1] **opprecon(cat, n, [file])**
- [2] **opprecon(cat, s, [file])**
- [3] **opprecon(cat, v, [file])**
- [4] **opprecon(cp, i, [])**
- [5] **opprecon(cp, r, [directory])**
- [6] **opprecon(ls, f, [directory])**
- [7] **opprecon(ls, l, [])**

The definition of the Option Effects are also stored as strings of English words. This is merely a convenience for generation. The definitions will enable the generator to give more detail about the specific effect of some option. Each rule here contains (1) Command Name, (2) Option Name, and (3) Option Effect with an English description.

- [1] **opeffect(more,#,**
"set the window size to # lines").
- [2] **opeffect(more,c,**
"display each page after cleaning screen").
- [3] **opeffect(more,d,**
"prompt to hit space to continue at each screen").
- [4] **opeffect(cp,i,**
"prompt file name when overwriting").
- [5] **opeffect(cp,p,**
"preserve the modification information from the source").
- [6] **opeffect(cp,r,**
"copy each subtree rooted at that directory").

Option Name definitions are similar in spirit to the Command Effect specifications defined in the “Basic command representation” section above. However, the definitions here are for specific options. The option definitions have three arguments: (1) Option Effect defined as an action(object) specification, (2) the Command Name, and (3) Option Name. The first three rules [1],[2] and [3] show the option variations on “cat”. The various options allow the displaying of file contents in a specific manner. We also show the options for “ls” (rules [4]-[10]) and for “cp” (rules [11]-[13]). Note that a characteristic of options is that sometimes they have the same action as the main action (e.g. display and display(non-printing-characters)) while other times they have a different action (e.g. display and squeeze(blanklines)).

- [1] **opcomm(number(lines), cat, n)**
- [2] **opcomm(squeeze(blank-lines), cat, s)**
- [3] **opcomm(display(non-printing-characters), cat, v)**
- [4] **opcomm(include(hidden-files), ls, a).**
- [5] **opcomm(display(directory-name), ls, d).**
- [6] **opcomm(display(directory-content), ls, f).**
- [7] **opcomm(display(group-ownership), ls, g).**
- [8] **opcomm(display(long-listing), ls, l).**
- [9] **opcomm(sort(file-ages), ls, t).**
- [10] **opcomm(display(subdirectories), ls, R).**
- [11] **opcomm(prompt(overwriting), cp, i).**

- [12] **opcomm(preserve(modification-information), cp, p).**
- [13] **opcomm(copy(subdirectories), cp, r).**

Concept representation

DataCon also contains a set of definitions of the possible concepts which a user may wish to ask about. Such concepts are considered to be Operating System objects like files and directories, and concepts like piping and filtering. Concept representations are three place lists with (1) Concept name, (2) Concept name pluralized, and (3) English description of concept. We show the definitions for , “ada”, “working directory” and “unix” here.

- [1] **con([ada],[ada],**
"Ada is developed on behalf of the U.S. Department of Defense for use in embedded systems. Ada is the first practical language to bring together important features such as data abstraction, multitasking, exception handling, encapsulation and generics.").
- [2] **con([working, directory],[working, directories],**
"The directory you are working in.").
- [3] **con([unix],[unix],**
"UNIX Operating System manages the resources of your computer system to perform useful work on your behalf. It is composed of three major parts: the kernel, the file system, and the shell.").

Plan representation

DataCon contains a list of possible Plans for command sequences which users may ask about. These command sequences are defined in terms of predicates which have five arguments. The first three arguments represent (1) an action, (2) an object, and (3) location of output. The last two arguments define the second action and its output location. We show two example rules below. Rule [1] represents displaying directories on the screen and then on the printer, and Rule [2] likewise for files.

- [1] **plan(display,directory,screen,display,printer).**
- [2] **plan(display,file,screen,display,printer).**

NATURAL LANGUAGE UNDERSTANDING

The most important part of any program which acts as a natural language interface is the natural language understander. There must be some means of mapping a user query into a good meaning representation of that query. The problem, of course, is that there are very many ways of specifying queries in English. The first job of the natural language interface is to use some type of syntactic filtering which determines the type of query being asked. The filter will check queries for certain objects or phases and works as a fast mechanism for determining query type. The second job is that of determining the meaning of a query, or its content, once the type of query is determined. Let’s take a look at the two components of OSCON which tackle these two problems.

Parsing natural language queries (ParseCon)

The parser called ParseCon has the job of determining the type of query present. There are characteristic ways of asking certain types of queries and the parser checks for these. The parser checks for the four basic types of query described in section 1. The ParseCon module has lists of the characteristic ways which people use to ask queries about particular query types.

One of the query types checked for is what-is concept. There are a number of characteristic phrases which are used. Some of these are listed below. The first set of rules [1-4] and rules [1a-1e] define the syntax of what would come before and after some concept respectively. The second set of rules [6-11] only define possible uses of syntax before the concept but do not reflect any after-concept syntax.

- [1] **firstphrase**([what, does|X], o1).
- [2] **firstphrase**([what, a|X], o2).
- [3] **firstphrase**([what|X], o3).
- [4] **firstphrase**([what|X], o4).

- [1a] **secphrase**([mean|X], o1).
- [2b] **secphrase**([is|X], o2).
- [3c] **secphrase**([is|X], o3).
- [4d] **secphrase**([are|X], o3).
- [5e] **secphrase**([means|X], o4).

- [6] **wphrase**([what, is, a]).
- [7] **wphrase**([what, are]).
- [8] **wphrase**([what, is]).
- [9] **wphrase**([explain]).
- [10] **wphrase**([describe]).
- [11] **wphrase**([]).

Another query type checked for is what-is-effect. Here, again there are a number of possible characteristic phrases. We list some here. Similarly, there are rules for (i) what-is-precondition, (ii) what-is-syntax, (iii) what-is-command, (iv) what-is mentioned command, and (v) what-is mentioned concept queries. Of course, there are syntax rules which will be compatible for all query types. However, this is not a problem because there are other characteristics of query types which separate them out.

- [1] **firstdesc**([what|X], o1).
- [2] **firstdesc**([does|X], o2).
- [3] **firstdesc**([does|X], o3).

- [1a] **secdesc**([does|X], o1).
- [2b] **secdesc**([do|X], o2).
- [3c] **secdesc**([have|X], o3).

- [4] **desc**([what, happens, with|X]).
- [5] **desc**([result|X]).
- [6] **desc**([results|X]).
- [7] **desc**([uses, of|X]).
- [8] **desc**([effect, of|X]).

Determining query meaning (MeanCon)

The function of the MeanCon component of OSCON is to determine query meaning. This is obvious for most query types except for what-is-command queries. These queries involve complex phrasings of English to describe the effects which the user wishes to execute. The MeanCon component of OSCON has the function of determining the occurrence of objects in user queries. There are seven types of object searched for: (1) command name, (2) option name, (3) verb reference, (4) object, (5) object modifier, (6) object location, and (7) concept.

MeanCon has a predicate called **findcmd** which searches for command names. The mention of command name is a good indicator of the type of query being asked. If a command name is present this indicates that the query is probably about (1) command preconditions, (2) command effects, or (3) command syntax. MeanCon also has a predicate called **findopt** which searches for mention of option names in queries.

One of the most difficult types of user query to be understood by the system are what-is command for mentioned effect queries. These are queries where the user knows what he/she wishes to accomplish but does not know the command to do that. In these cases the user will specify, in English, some process, or effect, which he/she wants to be executed. The process/effect can be described with (1) a primary verb and (2) a secondary verb. The user will use a primary verb to describe the main action/command in question. A secondary verb may be used to describe a restriction on the main action/command. This restriction could be a definition of some option specification for the major command.

Therefore, MeanCon has algorithms which check for (i) Primary Verb, (ii) Primary Verb Object, (iii) Object Modifiers, and (iv) Locations. There are also algorithms which search for (i) Secondary Verb, and (ii) Secondary Objects which usually describe option effects.

In checking for what-is-command queries the user will usually specify some action with a verb. This will be followed by the mention of an object such as a "file" or "directory". There may be a modifier of the object such as "contents". The location of the object may also be specified such as "printer" or "screen" or "directory".

There's a predicate in MeanCon called **findverb** which searches for verbs in user queries. When a verb is located this will determine the major category of action/command. Therefore, the word "delete" will reference removing, "see" will reference displaying and so on. MeanCon uses the stored verb-action structures in KnowCon to find verbs in queries and their related action representations.

Another predicate called **findobj** searches for the object of a verb. Say, for example, the user had asked, "How do I see a file?" then the findverb predicate will locate the verb "see". The query is split up so that the phrase after the verb is checked for an object. The object "file" is located and marked.

More complex queries may include modifiers and locations. Take the query, "How do I see my file contents on

the screen?” In this case, the phrase “[.file contents on the screen?” is checked for an object by findobj. Then, “[.contents on the screen?” is checked for modifier by **findmod**. Findmod locates “contents” as a modifier.

A predicate called **findloc** checks for locations in queries. Locations include “screen”, “printer” and “directory”. In our example, “[.on the screen?” is checked for location and “screen” is uncovered.

MeanCon has a predicate called **findcon** which checks for concepts in user queries. For example, the existence for the concept, “ada” will denote a query asking about, “ada”.

RULES FOR SOLVING (SolveCon)

Now that we have defined the data available to OSCON before the system begins to process a query we move on to describe the rules which match user queries to database information. SolveCon determines the answer for a query by (1) building an uninstantiated Formal Query from the query, (2) matching this structure to the DataCon database, (3) retrieving data from the database, and (4) using the data to build an instantiated Formal Query which is passed back to the GenCon natural language generator. We shall describe the answering process in two steps: (1) the algorithm used by SolveCon to specify the query and to retrieve data from the database, and (2) the structure of instantiated Formal Queries returned by SolveCon to the GenCon generator.

The solving algorithm

The Solver basically searches queries for three types of information: (1) Command Names, (2) English Descriptions of command effects, and (3) Concepts. The search process is conducted in the following order.

[1] SolveCon checks to see if a command name is mentioned in the query. Then, (a) SolveCon checks if an option (e.g. -l) is mentioned. If (a) fails then (b) SolveCon checks if the query is which-option. This check is done by having ParseCon check the syntax of the query, having MeanCon check for an English Description of an option effect. If either (a) or (b) are satisfied SolveCon will retrieve from the database Option Preconditions, Option Effect, Option Syntax, and Option Name.

If (a) and (b) have both failed then (c) SolveCon checks if the query is a what-is-precondition, what-is-effect or what-is-syntax query. Here, SolveCon checks the syntax again using ParseCon. If (c) fails, then (d) SolveCon checks the query for what-is-mentioned-command query. ParseCon is involved here too. If either (c) or (d) are satisfied SolveCon will retrieve Command Preconditions, Command Effect, Command Syntax, and Command Name from the database. If (d) fails then SolveCon moves on to step [2].

[2] SolveCon checks the query semantics. In this case the user must have asked an English query with no command

names. (i) SolveCon has ParseCon check the syntax of the query. (ii) Then, SolveCon calls MeanCon to check for a Primary Verb, Verb Object, Modifier, and Location. SolveCon will retrieve Command Preconditions, Command Effect, Command Syntax, and Command Name from the database. Next, (iii) SolveCon has MeanCon check for a Secondary Verb (option action), and Secondary Verb Object. SolveCon will retrieve from the database Option Preconditions, Option Effect, and Option Syntax. If step [2] fails then SolveCon goes on to step [3].

[3] SolveCon checks the query semantics. In this case the user must have asked an English query involving no command names. Also, the query must be about command combinations, or pipes, otherwise step [2] would have passed. SolveCon checks for the existence of a command combination in the user query. SolveCon has MeanCon check for the existence of a sentence connector like “and”. If this occurs then it is possible that the query involves command combination. SolveCon then calls the SolveCon algorithm again for (1) the piece of the query before the connector, and (2) the piece of the query after the connector. The data returned from (1) and (2) is integrated. If [3] fails then SolveCon tries step [4].

[4] SolveCon checks query syntax through ParseCon. Then MeanCon searches for concepts mentioned in the query. Examples of such concepts are “ada” and “protection”.

Structures returned

The step of SolveCon which succeeds will return an instantiated Formal Query to the generator. In step [1], if cases (a) or (b) succeed, an instantiated Formal Query will be returned containing the following: (1) Option Preconditions, (2) Option Effect, (3) Option Syntax, (4) Option Name, and (5) Query Type. In step [1], if cases (c) or (d) succeed, the instantiated Formal Query contains: (1) Command Preconditions, (2) Command Effect, (3) Command Syntax, (4) Command Name, and (5) Query Type.

In step [2] the Formal Query returned will contain slots for: (1) Command Preconditions, (2) Command Effect, (3) Command Syntax, (4) Option Preconditions, (5) Option Effect, (6) Option Syntax, and (7) Query Type. The complete structure will be instantiated when step [2] involves options. However, only parts (1),(2),(3), and (7) are instantiated when there is no mention of options.

With step [3] a list containing two instantiated Formal Queries is returned. Each formal query will contain: (1) Command Preconditions, (2) Command Effect, (3) Command Syntax, (4) Command Name, and (5) Query Type.

In step [4] a Formal Query with three pieces of information is returned. The structure contains (1) the Concept Name, (2) Concept Description, and (3) Query Type.

NATURAL LANGUAGE GENERATION (GenCon)

The final phase of the OSCON program is to map an instantiated formal representation into an English answer. There are two types of answer which may be returned to the user: (1) Stored English sentences describing some concept which are contained in the DataCon knowledge base, and (2) English sentences mapped out from instantiated Formal Queries.

The natural language generator for the OSCON system is used to map instantiated formal queries into English answers. The generator has five primary components:

- [1] **psyntax**: gives the syntax for a command
- [2] **peffect**: gives the effect of some command
- [3] **pexample**: gives an example on the use of some command
- [4] **ppre**: gives the preconditions for some command
- [5] **ppipe**: gives the commands involved in some piping example and an example of the piping

For each of the major query types various configurations of printing components are used. There are three types of what-is-attribute query: (1) what-is-precondition, (2) what-is-effect, and (3) what-is-syntax. In these cases the components [1], [2], [3] and [4] are combined in order. Printing out the syntax for some command is trivial. The syntax is already stored in the DataCon knowledge base. This is just returned to the user. Printing out preconditions is quite trivial too as all GenCon has to do is to print those preconditions retrieved from the DataCon precondition information.

Generation for what-is-effect queries is more complex. GenCon will print command effects by (1) checking to see if the output should be in plan/pipe form, and if it is, then generating the answer in plan/pipe form; (2) generating the (a) Command Syntax, (b) Effect and (c) Preconditions for the command. The Effect is generated from the instantiated Formal Query produced by SolveCon which contains action, object, object modifier and object location. The latter information is generated in sentence form. Some interleaving information such as the output of prepositions between object modifier and location are handled too.

For what-is-command for effect queries the latter algorithm is used. For what-is-mentioned command components [1], [2], [3] and [4] are used. For what-is mentioned concept, the answer is output from a stored piece of text. Often users ask queries about commands as concepts. The generation of these is simple as the definitions of such concepts are just stored as English descriptions in the first place. Therefore, all GenCon has to do is to map the stored sentences into English answers. We have written a simple algorithm which maps the English text into pretty format on the screen.

AN EXAMPLE

In this section we show an example of how the query "How do I see my files with numbered lines?" is understood and answered by OSCON. First, SolveCon attempts to find out the type of query being asked. Initially, SolveCon tries step [1] to match the query as one mentioning a

command and there is no match. Then step [2] is tried and a match occurs. The query is a semantic one. ParseCon is called forth and a syntactic match is found. "How do I" matches the syntactic form [how, do, i] for what-command queries.

Next, SolveCon calls MeanCon which analyzes the meaning of the sentence. (i) Findverb checks for a verb and gets "see". From KnowCon, "display" is marked as the action. Then, (ii) findobj checks "How do I" and "my files with numbered lines" for objects. "Files" is matched as an object. Data from the query (i.e. **display(file,contents,*)**) is matched against the DataCon database Effects and a match is found with **display(file,contents,screen)**. This effect match from the query data to DataCon will allow SolveCon to retrieve (1) Command Preconditions ([file]), (2) Command Effect (display(file,contents,screen)), (3) Command Syntax (cat -n <filename>), and (4) Command Name (cat).

Next, the query is checked for existence of a secondary action. The findverb predicate retrieves "numbered" as a secondary action and its object is retrieved as "lines". This representation is matched against the option database and number(lines) from the query matches number(lines) in the Option Effect definition in the database. The DataCon database is referenced and (1) Option Preconditions, (2) Option Effect, and (3) Option Name are returned. The data retrieved is integrated to form an instantiated Formal Query which is passed to the generator. The representation for this query is as shown below.

```

query(display(file,contents,screen),    % Command Effect
  "with numbered lines",                % Option Effect
  [cat -n <filename>],                    % Syntax
  [file],                                 % Preconditions
  cat),                                   % Command Name
  -n).                                    % Option Name

```

The GenCon generator takes the Formal Query and maps it into an English answer. (i) psyntax will print out "cat -n <filename>", (ii) peffect will display "will display file contents on the screen.", and (iii) popeffect will display "with numbered lines." Therefore, the complete answer generated for this query is:

'cat -n <filename>' will display file contents on the screen with numbered lines.

CURRENT STATE OF THE IMPLEMENTATION

The OSCON program can now answer over 1000 English queries. The maximum time for a query answer is 2.5 seconds when the Sun computer is at low load. OSCON answers four major types of query (1) what-is-attribute of mentioned command, (2) what-is mentioned command, (3) what-is-command for mentioned effect, and (4) what-is-mentioned concept. There are three cases of type (1): (1) what-is-precondition (2) what-is-effect, and (3) what-is-syntax. In real terms this brings the query types covered up to six. The system answers the latter three query types with options and will soon answer the other types with

options. OSCON's database contains information on 40 UNIX and 40 MS-DOS commands with their respective preconditions, effects, syntax and command names. OSCON has 20 grammar rules for understanding the ways that users ask queries about categories of commands. OSCON also contains 10 plan sets for possible combinations of commands.

COMPARISON TO OTHER SYSTEMS

There are basically two other natural language consultants for Operating Systems. These are the Unix Consultant (UC), and the Sinix Consultant (SC).

The Unix Consultant (UC) (see Wilensky et al. 1984, 1986, 1988; Chin 1988) is a natural language consultation system for UNIX, and is in many ways similar in scope and intent to OSCON. However, there are some key differences: (1) While OSCON is a specialized system with the sole goal of providing detailed expert help, UC has the broader goal of studying knowledge representation and planning (as well as natural language understanding) at a basic level. As such, UC takes a fundamentally different approach to knowledge representation, in that employs a much more general knowledge representation and planning mechanism, with a somewhat cognitive flavor. UC contains only one knowledge base of Operating System concepts which must serve both the understanding and the solving phases of query resolution, while OSCON incorporates specialized representations for each function. Hence, UC must sacrifice some of the specialization built into OSCON.

(2) Not unexpectedly, an examination of the examples presented in Wilensky et al. (1986) suggests that UC will have to perform far more extensive procedures to solve a given query, and that it may not be able to answer some of the very detailed queries that OSCON will address; (3) UC is not intended to be a consultant which will help users migrating from one system to another. UC is a consultant for the UNIX Operating System. We do not claim that the UC system could not act as a consultant on other Operating Systems. We claim that the Berkeley team have not concerned themselves with putting information from more than one Operating System in their program; (4) It is a characteristic of computer Operating Systems that commands can be combined in various ways to execute complex processes. In Wilensky et al. (1986, p. 6-10) there are a number of examples of the queries which the UC system handles. These examples are intended to show the kinds and scope of requests answered by the system. None of the examples involve command compositions but operations of single commands. The UC system has no capability for answering complex natural language queries which involve command sequencing; UC and OSCON are not truly competitors, but rather systems with different emphases.

The Sinix Consultant (SC) (see Kemke 1986, 1987; Hecking et al., 1988) is a broad-based UNIX help system. It is similar to OSCON in that it is designed from the start to be an Operating System consultant rather than a more general system into which a UNIX model is embedded.

Although SC contains a rich knowledge base, which reflects the technical aspects of the domain as well as the users view of the system, the focus of SC, like UC, is to provide help on the use of individual commands, rather than the interconnection of several. Our knowledge representation of plans has more emphasis on answering complex queries. There is no mechanism whereby the SC system will understand complex command sequences. However, the authors do predict in Hecking et al. (1988) that future development of the SINIX Knowledge Base will include "combinators" for I/O-redirection and pipelining. The SC system has a dialogue modeling component, for (1) handling elliptical queries, and (2) anaphora.

There are several other consultation systems for Operating Systems, including CMS-HELP developed by Yun (1984), TVX by Billmers & Garifo (1985), Wizard (see Shrager & Finin 1982; Finin 1983), and USCSH by Matthews & Pharr (1987). However, all of these systems appear to be either far less ambitious in scope than OSCON, or else have a totally different emphasis. In particular, all appear to employ rather simple surface models of UNIX.

CONCLUSION AND FURTHER WORK

It is concluded that it is possible to build a computer program which will answer natural language user queries about Operating Systems. We have shown how this is done by the OSCON system. The OSCON program answers over 1000 English queries in English. Each query is answered within seconds.

The development of any program like OSCON is enhanced if the program is built in a modular form where each module has a distinct function. This has been done for OSCON which is divided up into six distinct modules. This methodology allows for easy update of the program and also will allow the possibility of mapping the program over to a new domain.

In comparing OSCON to the other three systems available today OSCON turns out to have a different emphasis. The OSCON system is more concerned with the detail of Operating Systems and natural language processing rather than an experiment on cognitive modeling. Also, OSCON is the only system which answers queries involving command combinations.

There are three areas of further work proposed for OSCON which are all part of a dialogue interface to be added to the system. These are: (1) context storage mechanisms, (2) reference determination algorithms, and (3) user modeling capabilities (see Chin, 1988). Dialogue management is important and it will permit the user to ask queries without having to spell the queries out in elaborate English. Initial thoughts on this research are reported in Ball et al. (1989).

ACKNOWLEDGEMENTS

We would like to thank Zhaoxin Pan for programming parts of OSCON. Also, Hans Brunner, Andy Parng and Scott Wolff of the Intelligent Customer Assistance Project at U S WEST Advanced Technologies are thanked for

consultations on this research.

REFERENCES

- Ball, Jerry, John A. Barnden, Sylvia Candelaria de Ram, David Farwell, Louise Guthrie, Cheng-Ming Guo, Stephen Helmreich, Paul Mc Kevitt, Liu Min (1989) *The need for belief modelling in natural language processing*. In Proc. of the International Conference on Cross-Cultural Communication (ICC-CC-89), Trinity University, San Antonio, Texas, March.
- Billmers, Meyer A. & Michael G. Carifio (1985) *Building knowledge-based operating system consultants*. Proceedings of the Second Conference on Artificial Intelligence Applications, pp. 449-454, Miami Beach, December.
- Chin, David (1988) "Exploiting user expertise in answer expression" In Proceedings of the Seventh National American Conference on Artificial Intelligence (AAAI-88), St. Paul, Minnesota, Vol. 2, 756-760, August.
- Douglass, R. & Hegner, Stephen J. (1982) "An expert consultant for the UNIX operating system: Bridging the gap between the user and command language semantics". In Proceedings of the CSCSI/SCIEO, Conference 1982, Saskatoon, Saskatchewan, 92-96, May.
- Finin, Timothy W. (1983) *Providing help and advice in task oriented systems*. Proceedings of the Eighth International Joint Conference on Artificial Intelligence (IJCAI-83), Karlsruhe, West Germany, pp. 176-178.
- Hecking, M. C. Kemke, E. Nessen, D. Dengler, M. Gutmann & G. Hector (1988) "The SINIX consultant — a progress report" Memo Nr. 28, Universitat des Saarlandes, FB 10 Informatik IV, Im Stanwald 15, D — 6600 Saarbrücken 11, Fed. Rep. of Germany, August.
- Hegner, Stephen J. (1988) *Representations of command language behavior for an operating system expert consultation facility*. In "Intelligent Help Systems for UNIX — Case Studies in Artificial Intelligence" Peter Norvig, Wolfgang Wahlster & Robert Wilensky (Eds.), Heidelberg: Springer-Verlag Symbolic Computation Series.
- Hegner, Stephen J. & Douglass, Robert J. (1984) *Knowledge base design for an operating system expert consultant*. Proc. of the Fifth National Conference of the Canadian Society for Computational Studies of Intelligence (CSCSI), London, Ontario, December, 159-161.
- Kemke, Christel (1986) *The SINIX Consultant — Requirements, Design, and Implementation of an intelligent Help System for a UNIX Derivative*. Universitat des Saarlandes, KI-Labor (SC-Project), Bericht Nr. 11, October.
- Kemke, Christel (1987) *Representation of domain knowledge in an intelligent help system*. In Human-Computer Interaction — INTERACT '87, H.J. Bullinger and B. Shakel (Eds.), pp. 215-220. Amsterdam: Elsevier Science Publications B.V. (North-Holland).
- Matthews, Manton & Walter Pharr (1987) *Knowledge acquisition for active assistance*. Preprints of the First International Workshop on Knowledge representation in the UNIX help domain, University of California, Berkeley, California, December.
- Mc Kevitt, Paul (1986) *Formalization in an English interface to a UNIX database*. Memoranda in Computer and Cognitive Science, M CCS-86-73, Computing Research Laboratory, Dept. 3CRL, Box 30001, New Mexico State University, Las Cruces, NM 88003-0001.
- Mc Kevitt, Paul (1988) *Rules of inference in an operating system consultant*. In Proc. of the First Irish National Conference on Artificial Intelligence and Cognitive Science (AI/CS-88), Vol. 1, University Industry Center, University College Dublin, Dublin, Eire (Republic of Ireland), September.
- Mc Kevitt, Paul & Yorick Wilks (1987) *Transfer Semantics in an Operating System Consultant: the formalization of actions involving object transfer*. In Proceedings of the Tenth International Joint Conference on Artificial Intelligence (IJCAI-87), Vol. 1, 569-575, Milan, Italy, August.
- Selfridge, Peter G. (1988) "How to print a file: An expert system approach to software knowledge representation" In Proceedings of the Seventh National American Conference on Artificial Intelligence (AAAI-88), St. Paul, Minnesota, Vol. 2, 380-385, August.
- Shrager, Jeff & Tim Finin (1982) *An expert system that volunteers advice*. Proceedings National Conference on Artificial Intelligence (AAAI-82), pp. 339-340
- Wilensky, Robert; Arens, Yigal & Chin, David (1984) *Talking to UNIX in English: An overview of UC*. Communications of the ACM, Vol. 27, No. 6, June, 574-593.
- Wilensky, Robert; Mayfield, Jim; Albert, Anthony; Chin, David; Cox, Charles; Luria, Marc; Martin, James and Wu, Dekai (1986) *UC — a progress report*. Report No. UCB/CSD 87/303, Computer Science Division (EECS), University of California, Berkeley, California 94720, July.
- Wilensky, Robert; David N. Chin, Marc Luria, James Martin, James Mayfield and Dekai Wu (1988) *The Berkeley UNIX Consultant project*.

Computational Linguistics, Vol. 14, No. 4,
35-84, December.

Yun, David Y & David Loeb (1984) *The CMS-HELP expert system*. Proceedings International Conference on Data Engineering, IEEE Computer Society, 459-466, Los Angeles.

APPENDIX A

This appendix contains a list of some of the queries which OSCON[1.2] currently answers. The maximum time taken to answer any query is 2.5 seconds. The query sets have been divided into four major types (1) what-is-attribute of mentioned command, (2) what-is mentioned command, (3) what-is-command for mentioned effect, and (4) what-is mentioned concept.

| ?- oscon.
OSCON Program 1.0 (Sun-3, Sun Unix 4.2)
Copyright (C) 1988, Computing Research Laboratory.
All rights reserved.
Dept. 3CRL, Box 30001, NMSU, Las Cruces, NM (505) 646-5466
U S WEST Advances Technology
Please input your question ending with a '?'
Write 'quit.' when you are finished

;;;;;;;;;;;;;;;;;;;;;;;;; what-is-effect

--> what does ls do?
'ls <directoryname>' will display directory contents on the screen.

--> what happens with rm?
'rm <filename>' will remove a file from your current directory.

--> what is the effect of date?
'date' will display a date on the screen.

--> what does more -c do?
'more -c' will display each page after clearing the screen.

;;;;;;;;;;;;;;;;;;;;;;;;; what-is-syntax

--> what is the syntax of rm?
It has the syntax 'rm <filename>'.

--> How do i use cp?
It has the syntax 'cp <file1> <file2>'.

--> how does he use more?
It has the syntax 'more <filename>'.

;;;;;;;;;;;;;;;;;;;;;;;;; what-is mentioned command

--> what is ls?
'ls' is a command.
It has the syntax 'ls <directoryname>'.
'ls <directoryname>' will display directory contents on the screen.

--> what is more?
'more' is a command.
It has the syntax 'more <filename>'.
'more <filename>' will display file contents on the screen.
'more' only takes the argument 'file'

;;;;;;;;;;;;;;;;;;;;;;;;; what-is-command for mentioned effect

--> how do i see my file?
'more <filename>' will display file contents on the screen.

--> how do i see my file on the screen?
'more <filename>' will display file contents on the screen.

--> how do i see my file on the printer?
'lpr <filename>' will display file contents on the printer.

--> how do i see all my files?
'more <filename>' will display file contents on the screen.

'ls <directoryname>' will display directory contents on the screen.

--> how do i see this file?
'more <filename>' will display file contents on the screen.

--> how do i see that file?
'more <filename>' will display file contents on the screen.

--> how do i see his files?
'more <filename>' will display file contents on the screen.
'ls <directoryname>' will display directory contents on the screen.

--> how do i read my files?
'more <filename>' will display file contents on the screen.
'ls <directoryname>' will display directory contents on the screen.

;;;;;;;;;;;;;;;;;;;;;;;;; what-is-command for mentioned effect

--> how do i list my files and print my files?
'more <filename>' will display file contents on the screen.
'lpr <filename>' will display file contents on the printer.
To display file contents on the printer use 'more <filename> | lpr'

;;;;;;;;;;;;;;;;;;;;;;;;; what-is concept

--> what are aliases?
alias is the ability to establish shorthand names
for frequently used but long-winded commands.

--> quit.
over
yes
| ?-